

## 1/8" I.D. Feed & Supply Line Connect Hose & Fittings

Commonly used for connection between remote grease fitting and lubrication point or for connection between lubrication valve or injector and lubrication point on centralized lube systems.



### Hose

1/8" Supply and Feed Line Hose						
Part No.	Length (coils)	Nominal Size		Working Pressure	Minimum Bend Radius	Construction
		I.D.	O.D.			
241286	26 ft.	1/8"	5/16"	4,000 PSI	3 1/2"	Nylon Tube Dacron Braid Polyurethane Cover
241287	35 ft.					
241288	40 ft.					
252717	200 ft.					



**No. 246002**

Field Installable Hose End – NPT Swivel		
Part No.	Thread Size	Description
246002	1/8" NPT(M) Swivel	Field installable hose end with 1/8" NPT male thread swivel end.
Note: Swivel ends are for assembly purposes only. Not for use as live swivels on rotating components.		

## 1/8" I.D. Feed & Supply Line Connect Hose & Fittings

Commonly used for connection between remote grease fitting and lubrication point or for connection between lubrication valve or injector and lubrication point on centralized lube systems.

Field Installable Hose End Components	
Part No.	Description
272427	Hose end socket – plated steel
272401	Hose stud straight – for use with Quicklinc push-to-connect fittings
272394	Hose stud 90 degree – for use with Quicklinc push-to-connect fittings Plated Steel
272438	Hose end socket – stainless steel
274239	Hose stud straight – for use with Quicklinc push-to-connect fittings Stainless Steel



No. 272427



No. 272401



No. 272394



No. 272438



No. 274239