

Hydraulic Steel Tubing

20 Ft. Lengths

Lubricant Supply & Feed Line

Hydraulic Steel tubing is typically used for non-corrosive fluids such as hydraulic oil, engine oil, transmission fluids, gear lubricants, grease, etc.

SF" is an abbreviation for "Safety Factor".

Part Numbers show with an * are normally stocked items.



| Part No. | Tube O.D. | Wall Thickness | Length | Maximum WORKING PRESSURE @ 2:1 SF (psi) | Maximum WORKING PRESSURE @ 4:1 SF (psi) | Maximum WORKING PRESSURE @ 6:1 SF (psi) | Burst Pressure (psi) |
|----------|--------------|----------------|------------------------|---|---|---|----------------------|
| 62175 | 1/8" | 0.02 | 25' coil | 4,400 psi maximum working pressure | | | |
| TC-12 | 5/32" (4 mm) | NA | 12' coil | Copper tube used on Trico, Bijur, Shawa, Lube USA, etc. oil lubrication systems | | | |
| HT03-035 | 3/16" | 0.035 | 20 ft. straight length | 10,267 | 5,133 | 3,422 | 20,533 |
| HT04-035 | 1/4" | 0.035 | 20 ft. straight length | 7,700 | 3,850 | 2,567 | 15,400 |
| HT04-049 | 1/4" | 0.049 | 20 ft. straight length | 10,780 | 5,390 | 3,593 | 21,560 |
| HT05-049 | 5/16" | 0.049 | 20 ft. straight length | 8,624 | 4,312 | 2,875 | 17,248 |
| HT05-065 | 5/16" | 0.065 | 20 ft. straight length | 11,440 | 5,720 | 3,813 | 22,880 |
| HT06-049 | 3/8" | 0.049 | 20 ft. straight length | 7,187 | 3,593 | 2,396 | 14,373 |
| HT06-065 | 3/8" | 0.065 | 20 ft. straight length | 9,534 | 4,767 | 3,178 | 19,067 |
| HT08-049 | 1/2" | 0.049 | 20 ft. straight length | 5,390 | 2,695 | 1,797 | 10,780 |
| HT08-065 | 1/2" | 0.065 | 20 ft. straight length | | | | |
| HT08-083 | 1/2" | 0.083 | 20 ft. straight length | 7,150 | 3,575 | 2,383 | 14,300 |
| HT10-049 | 5/8" | 0.049 | 20 ft. straight length | | | | |
| HT10-065 | 5/8" | 0.065 | 20 ft. straight length | 5,720 | 2,860 | 1,907 | 11,440 |
| HT10-083 | 5/8" | 0.083 | 20 ft. straight length | | | | |
| HT10-095 | 5/8" | 0.095 | 20 ft. straight length | 6,967 | 3,483 | 2,322 | 13,933 |
| HT12-049 | 3/4" | 0.049 | 20 ft. straight length | 3,594 | 1,797 | 1,198 | 7,187 |
| HT12-065 | 3/4" | 0.065 | 20 ft. straight length | 4,767 | 2,383 | 1,589 | 9,533 |
| HT12-095 | 3/4" | 0.095 | 20 ft. straight length | 6,967 | 3,483 | 2,322 | 13,933 |
| HT12-109 | 3/4" | 0.109 | 20 ft. straight length | 7,994 | 3,997 | 2,665 | 15,987 |
| HT16-065 | 1" | 0.065 | 20 ft. straight length | 3,575 | 1,788 | 1,192 | 7,150 |
| HT16-095 | 1" | 0.095 | 20 ft. straight length | 5,225 | 2,613 | 1,742 | 10,450 |
| HT16-120 | 1" | 0.120 | 20 ft. straight length | 6,600 | 3,300 | 2,200 | 13,200 |
| HT20-095 | 1 1/4" | 0.095 | 20 ft. straight length | 4,180 | 2,090 | 1,393 | 8,360 |
| HT20-120 | 1 1/4" | 0.120 | 20 ft. straight length | 5,280 | 2,640 | 1,760 | 10,560 |

PRO/MARK INDUSTRIALS

Div. R.D. Lewis Sales Limited

Lubrication Systems & Devices

P.O. Box 26028, Cambridge, Ont. N1R 8E8 Phone (519) 621-0479 (800) 263-9865 Fax. (519) 621-1972 E-mail: sales@promarkindustrials.com