

Grease Gun Holders and Grease Fitting Couplers



Part No. NSP-149SP Grease Gun Holder

Provides for convenient, stationary mounting and holding of grease guns to machine, tool board, tool box, etc.



Part No. NSP-159 Heavy Duty Grease Gun Holder

Provides for convenient, stationary mounting and holding of grease guns to mobile equipment, trucks, machine, tool board, tool box, etc.



Grease Gun Loader Nipples

Loader fittings fit grease guns with 1/8" NPTF (f) port in head; simply remove plug and install. Loader couplers are used in conjunction with loader pumps to fill grease guns.

- LI-91108** loader nipple for Lincoln grease guns
- ALB396740** loader nipple for Alemite grease guns
- NSP80** loader nipple for National Spencer grease guns



Standard Grease Fitting Couplers

Part No. SAE-4JC1 with check valve
Part No. SAE-4JC2 no check valve
 10,000 psi maximum operating pressure
 Inlet 1/8" NPT(f)



Part No. SAE-36HD Heavy Duty Grease Fitting Coupler

Heavy duty couplers provide a quick leak proof connection with all grease fittings / hydraulic fittings. Built-in ball check prevents leak and lubricant backup.
 10,000 psi maximum operating pressure
 For all hydraulic type grease fittings
 Built in ball check prevents leak and lubricant back up.
 Inlet 1/8" NPT(f)



Part No. SAE-4J90C 90 Degree Grease Fitting Coupler

Grease fitting coupler SAE-4J90C is used to lubricate grease fittings in tight locations and eliminates the need to replace straight fittings with right-angled designs. This special access grease fitting coupler is often referred to as a 90 degree grease coupler, right angle grease coupler, or right angle grease adapter.
 Inlet 1/8" NPT(f)

Special Grease Fitting Couplers & Needle Nozzles



Part No. SAE-36SC Multiple Position Grease Fitting Coupler

7,000 psi maximum operating pressure Locks in any one of eight 45 degree positions. Built in swivel allows full 360 degree circle. Adjustable coupler section permits contact with fittings in reverse positions. Angle body has 1/8" NPT(f) inlet - permits addition of pipe extension.



Part No. SAE-SBC Slip Back Coupler

For adapting and quick on/off connection of any 1/8" NPT(M) extension nozzle or hydraulic coupler. Slip back hydraulic couplers are often referred to as locking sleeve hydraulic couplers, slip back couplers, or quick disconnect couplers.



Part No. NSP-10 6" Rigid Extension 1/8" NPT(m)



Part No. AL-B6238 Grease Extension Adapter

90 degree angle solves problem of contacting difficult to access fittings. Does not lock onto the grease fitting - applying pressure to the contact end of the adapter forms seal between built in rubber packing and grease fitting head. Includes SAE-SBC coupler



Part No. AL-B6239 Grease Gun Extension Adapter

For Difficult to Access Fittings. Straight extension. Use to lubricate recessed fittings where obstructions will not permit use of standard grease fitting couplers. Includes extension nozzle and SAE-SBC locking collar. Does not lock onto the grease fitting - applying pressure to the contact end of the adapter forms seal between the metal conical coupler face and the grease fitting head.



Part No. LI-5803 3" Needle Nozzle
Part No. LI-5806 6" Needle Nozzle

The needle nozzles allow operators to contact flush type grease fittings or difficult to access grease fittings.



Part No. AL-B6783 Needle Nozzle Adapter

The needle nozzle provides contact to flush type and difficult to access grease fittings. Includes the Lincoln 81980 locking collar for quick attachment to standard grease couplers and grease guns.



Part No. AL-B200 Injector Needle

For lubricating sealed bearings. Comes with plastic needle cover. For use with manual grease guns only.

Needle Adapters, Flush Fitting Nozzles, Button Head Couplers



Part No. **AL-B336770** Injector Needle
 Snaps into all standard grease couplers. Comes with plastic needle cover. For lubricating sealed bearings and CV joints.
 For use with manual grease guns only.



Part No. **AL-B411** Rubber Tipped Adapter
 To contact flush type or difficult to access grease fittings



LI-83278 Nozzle Adapter
 Includes rubber tip to contact flush type or difficult to access grease fittings. Includes SAE-SBC locking sleeve for quick attachment to standard grease couplers and grease guns.



Part No. **SAE-SFN** Flush Fitting Nozzle
 Used to lubricate standard flush type grease fittings / standard flush type zerk fittings. 1/8" NPTF thread



Standard Button Head Couplers
For use with 5/8" diameter standard button head fittings
 Standard button head couplers are used with 5/8" diam. standard button head grease fittings only. Our standard button head couplers pull on and/or push on to standard button head grease fittings.
Couplers with maximum working pressure 10,000 PSI
 Part No. **SAE-SBC-POP** 7/16"-27 thread (f) pull on/push on - steel insert
 Part No. **SAE-SBC-HPP** 1/8" NPT(f) pull on/push on - rubber insert/adapter
 Part No. **SAE-SBC-PUS1** 1/8" NPT(f) push on - rubber insert/adapter
 Part No. **SAE-SBC-PUS2** 7/16"-27 thread (f) push on - rubber insert
 Part No. **SAE-SBC-PUL1** 7/16"-27 thread (f) pull on - rubber insert
 Part No. **SAE-SBC-PUL2** M10 x 1 (f) pull on - rubber insert
 Part No. **SAE-SWIV-BHX** 1/8" NPT(F) swivel – pull on – 3,000 PSI maximum working pressure.



Giant Button Head Couplers
For use with 7/8" diameter standard button head fittings
 Part No. **SAE-GBC-PUL1** 7/16"-27 thread (f) pull on 15,000 PSI – rubber insert
 Part No. **SAE-GBC-PUL2** 1/8" NPT(f) pull on 10,000 PSI - rubber insert/adapter
 Part No. **SAE-GBC-PUL3** 1/4" PTF short (f) push on 15,000 PSI - rubber insert/adapter
 Part No. **SAE-GBC-PUS1** 7/16"-27 thread (f) push on 15,000 PSI - rubber insert
 Part No. **SAE-GBC-PUS2** 1/8" NPT(f) push on 15,000 PSI - rubber insert/adapter



Applied
 Lubrication
 Technology Inc.

Lubrication & Fluid Handling Solutions

7/16"-27 Adapters, Button Head Coupler Whip Hoses, Standard Whip hoses



Part No. SAE-BHA1 Button Head Coupler Adapter

7/16"-27 (f) x 1/8" NPT(m) 5,000 PSI

Adapts standard or giant button head couplers with a 7/16"-27 thread to hose assemblies and grease gun extensions with a 1/8" NPT connection



Part No. SAE-BHA2 Button Head Coupler Adapter

7/16"-27 (f) x 3/8" NPT(m) 5,000 PSI

Adapts standard or giant button head couplers with a 7/16"-27 thread to hose assemblies and grease gun extensions with a 3/8" NPT connection



Part No. AL-7089 Whip Hose Assembly With Standard Button Head Coupler

12" Hose, 1/8" NPT(m), SAE-SBC-HPP standard button head coupler
4,800 PSI maximum working pressure, 12,000 PSI burst pressure



Whip Hose Assemblies for Giant Button Head Couplers

Part No. AL-6704A - 12" Hose, 1/8" NPT(m), SAE-SBC-PUL1 giant button head coupler, 4,800 PSI maximum working pressure, 12,000 PSI burst pressure

Part No. AL-6704B - 18" Hose, 1/8" NPT(m), SAE-SBC-PUL1 giant button head coupler, 4,800 PSI maximum working pressure, 12,000 PSI burst pressure



Part No. AL-B337595-A1 1/8" NPT(m) 12" Whip Hose – 6,000 PSI Maximum working Pressure – Thermoplastic Construction

Part No. AL-B337595-B1 1/8" NPT(m) 18" Whip Hose – 6,000 PSI Maximum working Pressure – Thermoplastic Construction

Part No. AL-B317850-1 1/8" NPT(m) 12" Whip Hose – 4,800 PSI Maximum working Pressure – Elastomeric single wire braid hose

Part No. AL-317850-1F 1/8" NPT(m) 18" Whip Hose – 4,800 PSI Maximum working Pressure – Elastomeric single wire braid hose

Part No. AL-317850-2 1/8" NPT(m) 24" Whip Hose – 4,800 PSI Maximum working Pressure – Elastomeric single wire braid hose

Part No. AL-317850-3 1/8" NPT(m) 36" Whip Hose – 4,800 PSI Maximum working Pressure – Elastomeric single wire braid hose



Part No. LI-5812 1/8" NPT(m) 12" Whip hose – 4,500 PSI Maximum working pressure – Thermoplastic hose with spring guard.

Part No. LI-5818 1/8" NPT(m) 18" Whip hose – 4,500 PSI Maximum working pressure – Thermoplastic hose with spring guard.

WARNING

The above whip hoses are for use with hand-operated grease guns only. The pressure rating on these hose assemblies applies when used with hand-operated grease pumping equipment ONLY, such as grease guns or bucket pumps. DO NOT use with power-operated equipment. Rupture of the hose can result in serious injury such as fluid injection into the flesh. For powered equipment, refer to adapters and swivel devices, which can be safely used where rapid pressure rises are encountered.



Applied
Lubrication
Technology Inc.

Lubrication & Fluid Handling Solutions

Grease Coupler Kit



Part No. NSP-660 Coupler Kit

Includes:

Part No. AL--B6239 Grease Gun Extension Adapter

Part No. AL--B6783 Needle Nozzle Adapter

Part No. SAE-4J90C 90 Degree Grease Fitting Coupler with Part No. SAE-SBC Slip Black Coupler

Part No. AL-B200 Injector Needle

Quick connect 12" hose with coupler and spring guard

Attractive and durable nylon pouch

WARNING

Do not operate pumps, components or equipment at higher pressure than lowest rated part of system. Severe injury may result if equipment or components are operated at pressures greater than the lowest rated component in the distribution system.



Applied
Lubrication
Technology Inc.

Lubrication & Fluid Handling Solutions

12 French Drive, Orangeville, ON Technical Sales: Bob Lewis Cell: (519) 658-3204 E-Mail: bob@appliedlubrication.com